



John Deere 8RX 410

~~445.000€~~ 425.000€

DESCRIPTION

2023, Signature Edition, John Deere PowerTech PSS 9.0 L engine, John Deere eAutoPowr gearbox, 40 km/h, **Starfire 6000** integrated receiver StarFire 6000

TECHNICAL SPECIFICATIONS

Year of manufacture: 2023

Number of working hours of the engine: 170

Horsepower: 410

Working capacity of the engine: 9000 ccm

Number of cylinders: 6

Engine type: John Deere PowerTech PSS

Transmission: John Deere eAutoPowr

Maximum speed: 40 km/h

PTO: 100/1000E

Machine mass: 18700 kg

Hydraulic pump: 318 l/min

CABIN

Cabin suspension, driver's seat with air suspension, and lumbar support. The CommandPro joystick for the tractor control provides options such as programming 2 operating speeds, speed adjustment via wheel tuning, cruise control, quick direction change, acceleration adjustment, and a total of 3 programming buttons + 4 switches Ultimate equipment package (includes leather-lined seat, with massage function, ventilation and heating, electronically adjustable functions, the ability to rotate the seat 40° to the right and 25° to the left, height-adjustable leather-covered steering wheel with possibility to memorize position, Touchscreen radio with 16 cm display and Premium sound system, front, rear and right-positioned wiper with washing function and blinds, compartment under the passenger seat, 230V socket, 3 - 12V sockets, 6 - 12V three pin sockets, 4 USB ports, laminated glass, passive noise reduction system, factory preparation for cameras). CommandArm control on the electrically adjustable wide-angle mirrors, folding passenger seat, radio package, air conditioning, external connectors for ignition assistance with cables, rear cable passage, front and rear windshield wiper with washing function, front and rear sunshade, interior lighting, clothes hook, rubber mat, tilting cabin, 330° all-round visibility, telescopic tilting steering wheel, 69 dB(A), factory camera preparation.

HYDRAULICS AND PTO

PFC hydraulic system (pressure and flow compensation), dual pump, flow rate 318 l/min, maximum pressure 204 bar, 5 pairs of SCV with electro-hydraulic control, additional hydraulic oil return outlets, additional hydraulic 3/4" Power Beyond outlets

WHEEL DIMENSIONS

Front tracks 610 mm, Camso® RD series 4500

Rear tracks 762mm, Camso® RD Series 4500

LIGHTS AND ELECTRONICS

Ultimate LED lighting package, 360° LED lighting coverage provided by 22 LED working lights.

alternator 330 A, main electric circuit switch

AMS

Integrated StarFire 6000 receiver with SF1 signal with a maximum deviation of +/- 15 cm

Generation 4 CommandCenter 4600 10" display 10 (26 cm Touchscreen) with additional 4600 10" display (26 cm Touchscreen)

Automation activation 4.0 (includes AutoTrac, Sectional control, Row Sense, wireless data transmission, passive attachment guidance, Gen 4600 display synchronization in AutoPath™)

JDLink Connect advanced package with 2 years of free promotion, JDLink telematics solution enables advanced monitoring of fuel consumption, AdBlue consumption, machine movement, current and past machine location, engine temperature, and AutoTrac use. RDA - allows remote access to the machine display to easily set up the machine and eliminate possible errors.

MyOperation Centar

ADDONS

Fuel water separator, front mudguards 610 mm, front weight carrier, 900 kg (18x50 kg) front weights, air installation 2 - circular