













**John Deere T560** 

<del>123.000€</del> 118.250€



PSC Osijek Jablanova 16 31000 Osijek 031 297 341 **PSC Bjelovar** Bleiburških žrtava 22 43000 Bjelovar 046 226 440

# **DESCRIPTION**

2013, John Deere PowerTech PSX 9.0 I engine, 4×4 drive, John Deere 620R header (6.10 m) with trolley

### **TECHNICAL SPECIFICATIONS**

Year of manufacture: 2013.

First registration: 2013.

Number of working hours of the thresher: 1825

Number of working hours of the engine: 3025

Horsepower: 350

Working capacity of the engine: 9000 ccm

Number of cylinders: 6

Engine type: John Deere PowerTech PSX 9.0 I with turbocharger

Transmission: Gearbox with 3 speeds, with electric speed change, hydrostatic transmission

Maximum speed: 30 km/h

Grain hopper volume: 10000 l

Number of straw shakers: 5

Header width: 6.10 m

Fuel tank capacity: 800 I

# **HEADER**

Gearbox with 3 speeds, with electric speed change, hydrostatic transmission

Working width: 6.70 m

Hydraulic winch drive, winch tilt adjustment by lever, stainless steel plate at the bottom of the header, retractable auger fingers, epicyclic scythe drive, drive on the left side of the header, multi coupling for electric and hydraulic lines, winch with steel fingers, automatic winch speed depending on the speed of the harvester, 2 crop dividers.

Header trolley

#### CABIN

John Deere Premium cabin, heating, ventilation, air conditioning, radio, air-suspension driver's seat, front passenger seat, CommandTouch control console with GS3 CommandCenter 7" touchscreen control monitor, adjustable steering wheel, windshield wiper, storage compartments

### WHEEL DIMENSIONS

Tires: front 800/65R32, rear 480/65R30

# **FRONT AXLE**

4WD adjustable rear axle, 4x4 drive

### **TOWING HITCH**

Rear trolley drawbar for headers



PSC Osijek Jablanova 16 31000 Osijek 031 297 341 **PSC Bjelovar** Bleiburških žrtava 22 43000 Bjelovar 046 226 440

#### LIGHTS AND ELECTRONICS

Cabin roof working lights, platform working lights, grain bunker and unloading pipe lights, 3 rotating lights

### **AMS**

JDLink

# **ADDONS**

Unloading pipe 5.20 m, 105-degree rotating range and unloading speed of 88 l/sec, grain bunker 10,000 L, cutter bar with electric deflector adjustment, clean grain elevator bottom protection, hydraulically driven chaff spreaders, weight recovery laser monitoring

### OTHER INFORMATION

Average shipping weight (without header): 14.480 kg